




SPECIFICATIONS:

Light Output: 1080 LM/m (332 LM/ft.)
 Power: 14.4 Watts/m (4.4 Watts/ft.)
 Voltage: 12V
 Efficacy (Lumens per Watt): 75 LM/W
 Colour Accuracy (CRI): 80+
 Light Colour: 4000K Vibrant White
 Beam Angle: 120°
 Length: 16'-3" / 5m
 Width: 0-1/2" / 12mm
 Depth: 0-3/16" / 4mm
 Cuttable every 2" / 50mm
 Dimmable
 Waterproof IP67 (with sealed connections)
 50,000 Life Hours
 Included: 4 x Silicone End Caps per Roll

LIGHTING FACTS

HIGH DENSITY RIBBON

ITEM NO.	GLF-HD-12V-40K
Light Output (Lumens)	1400/M
Watts	14/M
Lumens per Watt (Efficacy)	100
Colour Accuracy	80+
Colour Rendering Index (CRI)	
Light Colour	4000K Vibrant White
	
2700K 3000K 3500K 4000K 4500K 5000K 6000K	
14 Watt/m • Vibrant White	

PHOTOMETRICS:



PRODUCT BENEFITS:

High density ribbon is perfect for many applications including kitchen undercounter, coves, niches, display cases/open shelving and more!

AVAILABLE ACCESSORIES:

12V Dimmable Drivers

25W • GLS-12025-TD
50W • GLS-12050-TD
100W • GLS-12100-TD
150W • GLS-12150-TD
200W • GLS-12200-TD

Quick Clip Feed

GLF-FEED

Quick Clip Flexible Joiner

GLF-FLEX

Aluminum Channels

Deep Recess • GLF-1201REC-1M
Deep Surface • GLF-1202SUR-1M
45° Angle • GLF-1203ANG-1M
Shallow Recess • GLF-1204RECS-1M
Shallow Surface • GLF-1205SURS-1M

Drywall Channel Lighting System**Chopstick Lighting System**