




GLK-15PAR30-3038 LIGHTING SPECS
Light Output (Lumens) 1500Lm±10%
Power 15 Watts
Lumens per Watt (Efficacy) 100
Colour Accuracy (CRI) 80+
Light Colour 3000k Warm White
LED Chip Epistar
Size $\Phi 90 \times 120$ (3.54" x 4.72")
Beam Angle 38°
Dimmable
35,000 Life Hours
10 Year Warranty



Lighting Specs	PAR30
ITEM NO.	GLK-15PAR30-3038
Light Output (Lumens)	1500
Watts	15
Lumens per Watt (Efficacy)	100
Colour Accuracy	80+
Colour Rendering Index (CRI)	
Light Colour	3000 (Warm White)
	
2700K 3000K 4500K 6500K	
15 Watt Warm White	

GLK-15PAR30-3038 PHOTO METRICS			
MOUNTING HEIGHT	CENTER BEAM FOOT CANDLES (FC)	EDGE OF BEAM FOOT CANDLES (FC)	BEAM AREA COVERED
6FT	86.3FC	38FC	4' 6"
8FT	46.9FC	28FC	6'
10FT	28.8FC	13FC	8'
12FT	20.2FC	8.8FC	9' 6"
14FT	15.4FC	6.4FC	11'
16FT	11.2FC	5.2FC	12' 6"
18FT	9.4FC	3.1FC	14'
20FT	7.7FC	2.1FC	15' 6"